

MicroStac

0.8 mm Connectors









MEZZANIN CONNECTOR SYSTEM

GENERAL



MicroStac connector series features hermaphroditic mating design within a pitch of 0.8 mm. Connectors and its mating connectors are identical. This reduces the bill of material and also storage and handling costs. Two contact points between mated contacts and the wipe length of up to 1.5 mm ensure a high reliability. The design calls for fast, fully automatic SMT assembly. MicroStac connectors are available for Board-to-Board heights of 3 mm and 5 mm. Despite its small size, MicroStac contacts offer large radiating surfaces to provide a high current rating.



CONCEPT

FEATURES

Pitch	0.8 mm		
No. of Pins	6, 9, 10, 12, 14, 50, 54		
Current rating per contact	up to 2.7 A		
Termination technology	SMT		
Applications	Stacked boards (Mezzanine)		
Board-to-Board height	3 mm, 5 mm		
Weight	0.18 g (6-pin version)		
Connectors	Single row connectors Dual row connectors		



Wipe length 5 mm board height: 1.5 mm 3 mm board height: 0 mm



CONCEPT –

CAPABILITIES

Stacked boards (Mezzanine) single row version (5 mm board height)





Stacked boards (Mezzanine) dual row version (5 mm board height)





ADVANTAGES

CONTACT DESIGN



- no difference between male and female connector
- contacts are based on a patented contact design; Patent-No.: DE 19 809 881; US 6,379,170
- two contact points for compensation of tolerances

EASY ASSEMBLY



- integrated pick and place surface for automatic assembly
- pick and place surface will hinge away when mated the first time (2-row versions)



ADVANTAGES

LOCATING PEGS



- geometrically heterogeneous locating pegs for precise positioning on the circuit board
- enables best possible compensation of PCB holes for both positive and negative tolerances

PROCESSING



- tape and reel packaging for transport safe packaging and fully automatic assembly
- fully automatic assembly and reflow soldering for efficient processing on modern assembly lines



MATING CONDITIONS FOR SINGLE ROW VERSIONS

ALLOWED INCLINATION FOR A SECURE SELF-CENTERING





1) depends on No. of Pins and misalignment tolerance

ALLOWED MISALIGNMENT TOLERANCES FOR A SECURE SELF-CENTERING







MATING CONDITIONS FOR DUAL ROW VERSIONS -

ALLOWED INCLINATION FOR A SECURE SELF-CENTERING





1) depends on No. of Pins and misalignment tolerance

ALLOWED MISALIGNMENT TOLERANCES FOR A SECURE SELF-CENTERING





CHARACTERISTICS

TECHNICAL DATA

Description	Standard	Single- and Dual-Row Connectors	
Climate category	DIN EN 60068-1 test b	-55 / 125 / 21	
Temperature range		-55 / 125 °C	
Current rating per contact	IEC60512 test 5b	50-pin version at 20 °C ambient temperature: 1.6 A	
Air- and creepage distance		contact - contact min. 0.4 mm	
Operating voltage	IEC 60664	The permissible operating voltages depend on the customer ap- plication and on the applicable or specified safety requirements. Insulation coordination according to IEC 60664-1 has to be re- garded for the complete electrical device. Therefore, the maxi- mum creepage and clearance distances of the mated connec- tors are specified for consideration as a part of the whole current path. In practice, reductions in creepage or clearance distances may occur due to the conductive pattern of the printed board or the wiring used, and have to be taken into account separately. As a result the creepage and clearance distances for the applica- tion may be reduced compared to those of the connector.	
Dielectric strength	IEC 60512 test 4a	contact – contact 500 Vms	
Contact resistance	IEC 60512 test 2a	< 10 mΩ	
Insulation resistance	IEC 60512 test 3a	$> 10^4 M\Omega$	
Vibration, sine	IEC 60512 test 6d	10 – 2000 Hz 20 g	
Contact disturbance (while vibration test)	IEC 60512 test 2e	< 1 µs	
Shock halfsine	IEC 60512 test 6c	50 g 11 ms	
Contact disturbance (while shock test)	IEC 60512 test 2e	< 1 µs	



CHARACTERISTICS

Description	Standard	Single- and Dual-Row Connectors	
Mechanical operation	IEC 60512 test 9a	< 10 mating cycles	
Insertion and withdrawal force	IEC 60512 test 13b	3 mm stack height: max. 4 N per contact 5 mm stack height: max. 2 N per contact	
Gauge retention force	IEC 60512 test 16e	> 0.15 N	
Processing Conditions			
Hand soldering temperature max.	IEC 60068-2-20	3.5 s at 350 °C	
Dip soldering temperature max.	IEC 60068-2-20	10 s at 260 °C	
Reflow soldering temperature max.	JEDEC J-STD-020	20 - 40 s at 260 °C	
Coplanarity	< 0.1 mm		
Housing Material			
Insulation body		PPA	
CTI value	IEC 112	> 600	
UL flame rating		UL 94 V-0	
UL file plastic material	E171666		
Contact Material			
Base material		Cu alloy	
Mating area		gold plating	
Termination area		Sn	
Environment Compatibility	/		
Recycling	no flame-retardent additives, no toxic additives allow easy recycling		



VERTICAL MALE, SINGLE ROW

PRODUCT SPECIFICATION



- pitch 0.8 mm
- SMT process compatible
- two contact points
- one part number for interconnection saving admin and logistic costs
- mated stacking height: 3 mm (wipe length: 0 mm) or 5 mm (wipe length: 1.5 mm)
- anti-magnetic versions available

DIMENSIONAL DRAWINGS



А В



VERTICAL MALE, SINGLE ROW -

ORDERING INFORMATION

No. of Pins	Mated Stacking Height	Termination	Packaging	Part Number
6	5	SMT	Tape and reel	114711
9	3	SMT	Tape and reel	224920
10	5	SMT	Tape and reel	354863
12	5	SMT	Tape and reel	114712
14	5	SMT	Tape and reel	284257

Anti-magnetic Versions

No. of Pins	Mated Stacking Height	Termination	Packaging	Part Number
12	5	SMT	Tape and reel	254168



VERTICAL, DUAL ROW

PRODUCT SPECIFICATION



- pitch 0.8 mm
- SMT process compatible
- two contact points
- one part number for interconnection saving admin and logistic costs
- mated stacking height: 5 mm (wipe length: 1.5 mm)
- anti-magnetic versions available

DIMENSIONAL DRAWINGS





VERTICAL, DUAL ROW

ORDERING INFORMATION

No. of Pins	Mated Stacking Height	Termination	Packaging	Part Number
50	5	SMT	Tape and reel	114713
54	5	SMT	Tape and reel	354000

Anti-magnetic Versions

No. of Pins	Mated Stacking Height	Termination	Packaging	Part Number
54	5	SMT	Tape and reel	484438



PART NUMBER INDEX

Part Number	Page
114711	12
114712	12
114713	14
224920	12
254168	12

Part Number	Page
284257	12
354000	14
354863	12
484438	14



ERNI Electronics GmbH & Co. KG

Seestrasse 9 73099 Adelberg Germany Tel +49 7166 50-0 Fax +49 7166 50-282 info@erni.com www.erni.com

ERNI Electronics Inc.

2201 Westwood Ave Richmond, VA 23230/USA Tel +1 804 228-4100 Fax +1 804 228-4099 info@erni.us

ERNI Asia Holding Pte Ltd.

23A Serangoon North Avenue 5 # 04-11 Singapore 554369 Tel +65 6 555 5885 Fax +65 6 555 5995 info.sg@erni.com

ERNI Electronics AG

Zürichstrasse 72 8306 Brüttisellen - Zürich Switzerland Tel +41 44 835 33 83 info@erni-electronics.ch

Europe South America Africa

North America Canada Mexico

Asia Australia New Zealand

Switzerland

© ERNI Electronics GmbH & Co. KG 2018 • Printed in Germany • A policy of continuous improvement is followed and the right to alter any published data without notice is reserved. ERNI®, ERNI WoR&D®, CONNECTED BY COMPETENCE®, MicroBridge®, MicroCon®, MicroStac®, MicroSpeed®, MiniBridge®, MiniMez®, MaxiBridge®, ERmet®, ERmet ZD®, ERmet ZDplus®, ERmet ZD HD®, ERbic®, ERNIPRESS®, INTERact® and BLUEcontact® are trademarks (registered or applied for in various countries) of ERNI Production GmbH & Co. KG.