




TKS 4/2 OG

1223.3



Transformer terminal, Screw connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 15 mm, Colour: Orange

Commercial

General

Colour: Orange

Country of origin: DE

Customs number: 85369010

Packaging unit: 25

Product description: Transformer terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 8.2g

Weight per piece (not including packaging): 7.8g

Technical

Dimensions

Height: 33.1mm

Length: 20.5mm

Width: 15mm

Ratings

Contamination degree: 3

Maximum power dissipation for nominal condition: 2.05W

Overvoltage category: III

Rated cross-section: 4mm²

Rated current: 32A

Rated impulse voltage: 8kV

Rated voltage: 800V

Connection data

Connection principle: Screw connection

Connections: 2

Screw head: Slotted

Screw threading: M 3

Stripping length: 9mm

Tightening torque, max.: 1Nm

Tightening torque, min.: 0.5Nm

Wire cross-section AWG, max.: 10

Wire cross-section AWG, min.: 22

Wire cross-section single core (rigid)/stranded, max.: 6mm²

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm²

Wire cross-section stranded with wire-end ferrules, max.: 4mm²

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm²

Wire cross-section stranded, max.: 6mm²

Wire cross-section stranded, min.: 0.2mm²

Further technical data

Gauge plug acc. to EN 60 947-1: A4

Mounting type: Custom profile

Number of test pick-off options: 2

Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

Approvals

Standards and regulations

EAC approval: TR ZU 004/2011

EAC approval granted:

KEMA KEUR approval

KEMA KEUR approval: EN 60947-7-1:2009

KEMA KEUR approval granted:

KEMA rated current: 32A

KEMA rated impulse voltage (fuse holder without electrical components): 8kV

KEMA rated voltage: 800V

KEMA torque, max.: 1Nm

KEMA torque, min.: 0.5Nm

KEMA wire cross-section single core (rigid), min.: 0.2mm²

KEMA wire cross-section single-core (rigid), max.: 6mm²

KEMA wire cross-section stranded, max.: 6mm²

KEMA wire cross-section stranded, min.: 0.2mm²

UL Recognized

UL File Number: E95701

UL Recognized: 1

UL Usegroup B: rated current: 27A

UL Usegroup B: rated voltage: 600V

UL Usegroup C: rated current: 27A

UL Usegroup C: rated voltage: 600V

UL approval: UL 1059

UL factory wiring:

UL field wiring:

UL torque, max.: 8.85Lb In.

UL torque, min.: 4.4Lb In.

UL wire cross-section single-core (rigid) AWG, max.: 10

UL wire cross-section single-core (rigid) AWG, min.: 22

UL wire cross-section stranded AWG, max.: 10

UL wire cross-section stranded AWG, min.: 22

UL wire material: Cu

Environment

Environmental Product Compliance

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2024-06-27

RoHS Conform: Yes

Accessories

Quick marking



PMC SB 7,5/40 WH
[9326.7](#)

Markers



PMC SB 7,5/40 So WH
[3327.7](#)
