


# TKS 4/SI 6,3x32 OG

17031.3



EAC



Transformer-fused terminal, Screw connection, Mounting type: Custom profile, Rated cross-section: 4 mm<sup>2</sup>, Width: 12.5 mm, Colour: Orange

## Commercial

### General

Colour: Orange

Country of origin: DE

Customs number: 85369010

Packaging unit: 50

Product description: Transformer-fused terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 12.6g

Weight per piece (not including packaging): 12.2g

---

## Technical

---

### Dimensions

---

Height: 43.9mm

Length: 28.3mm

Width: 12.5mm

---

### Ratings

---

Contamination degree: 3

Overvoltage category: III

Rated cross-section: 4mm<sup>2</sup>

Rated current: 32A

Rated impulse voltage: 4kV

Rated voltage: 500V

---

### Connection data

---

Connection principle: Screw connection

Connections: 1

Screw head: Slotted

Screw threading: M 3

Stripping length: 8mm

Tightening torque, max.: 1Nm

Tightening torque, min.: 0.5Nm

Wire cross-section AWG, max.: 10

Wire cross-section AWG, min.: 22

Wire cross-section single core (rigid)/stranded, max.: 6mm<sup>2</sup>

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, max.: 4mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded, max.: 6mm<sup>2</sup>

Wire cross-section stranded, min.: 0.2mm<sup>2</sup>

---

### Further technical data

---

Fuse size: 6,3 x 32mm

Gauge plug acc. to EN 60 947-1: A4

Mounting type: Custom profile

---

Power loss in compound arrangement - only short-circuit protection, max.: 2,5 / 2,5W / A

Power loss in compound arrangement - overload and short-circuit protection, max.: 2,5 / 2,5W / A

Power loss in singular arrangement - only short-circuit protection, max.: 4 / 10W / A

Power loss in singular arrangement - overload and short-circuit protection, max.: 2,5 / 2,5W / A

Voltage fuse: 250V

## Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

## Approvals

---

### Standards and regulations

EAC approval: TR ZU 004/2011

EAC approval granted:

### KEMA KEUR approval

KEMA KEUR approval: EN 60947-7-3:2009

KEMA KEUR approval granted:

KEMA fuse size: 6,3 x 32mm

KEMA power loss in compound arrangement - only short-circuit protection, max.: 2,5 / 2,5W / A

KEMA power loss in compound arrangement - overload and short-circuit protection, max.: 2,5 / 2,5W / A

KEMA power loss in singular arrangement - only short-circuit protection, max.: 4 / 10W / A

KEMA power loss in singular arrangement - overload and short-circuit protection, max.: 2,5 / 2,5W / A

KEMA rated current: 10A

KEMA rated impulse voltage (fuse holder without electrical components): 8 (4)kV

KEMA rated voltage: 500V

KEMA torque, max.: 1Nm

KEMA torque, min.: 0.5Nm

KEMA voltage fuse, max.: 250V

KEMA wire cross-section single core (rigid), min.: 0.2mm<sup>2</sup>

KEMA wire cross-section single-core (rigid), max.: 6mm<sup>2</sup>

KEMA wire cross-section stranded, max.: 6mm<sup>2</sup>

KEMA wire cross-section stranded, min.: 0.2mm<sup>2</sup>

### UL Recognized

---

UL File Number: E95701

UL Recognized: 1

UL Usegroup B: rated current: 30A

UL Usegroup B: rated voltage: 600V

UL Usegroup C: rated current: 30A

UL Usegroup C: rated voltage: 600V

UL approval: UL 1059

UL factory wiring:

UL field wiring:

UL torque, max.: 8.85Lb In.

UL torque, min.: 4.4Lb In.

UL wire cross-section single-core (rigid) AWG, max.: 10

UL wire cross-section single-core (rigid) AWG, min.: 24

UL wire cross-section stranded AWG, max.: 10

UL wire cross-section stranded AWG, min.: 24

UL wire material: Cu

---

## Environment

---

### Environmental Product Compliance

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2024-06-27

RoHS Conform: Yes

---

## Accessories

---

## Quick marking

---



**PMC SB 7,5/40 WH**

9326.7

---

## Markers

---



**PMC SB 7,5/40 So WH**

3327.7

---