



EAC

M4



Transformer terminal, Screw connection, Mounting type: Custom profile, Rated cross-section: 10 mm², Width: 22.5 mm, Colour: Red

Commercial

General

Colour: Red

Country of origin: CZ

Customs number: 85369010

Packaging unit: 50

Product description: Transformer terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 30.54g

Weight per piece (not including packaging): 30.14g

Technical

Dimensions

Height: 39.5mm

Length: 37.5mm

Width: 22.5mm

Ratings

Contamination degree: 3

Maximum power dissipation for nominal condition: 3.65W

Overvoltage category: III

Rated cross-section: 10mm²

Rated current: 57A

Rated impulse voltage: 8kV

Rated voltage: 800V

Connection data

Connection principle: Screw connection

Connections: 2

Screw head: Slotted

Screw threading: M 4

Stripping length: 14mm

Tightening torque, max.: 2Nm

Tightening torque, min.: 1.2Nm

Wire cross-section AWG, max.: 6

Wire cross-section AWG, min.: 24

Wire cross-section single core (rigid)/stranded, max.: 16mm²

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm²

Wire cross-section stranded with wire-end ferrules, max.: 10mm²

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm²

Wire cross-section stranded, max.: 16mm²

Wire cross-section stranded, min.: 0.2mm²

Further technical data

Gauge plug acc. to EN 60 947-1: B6

Mounting type: Custom profile

Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

Approvals

Standards and regulations

EAC approval: TR ZU 004/2011

EAC approval granted:

KEMA KEUR approval

KEMA KEUR approval: EN 60947-7-1:2009

KEMA KEUR approval granted:

KEMA rated current: 57A

KEMA rated impulse voltage (fuse holder without electrical components): 8kV

KEMA rated voltage: 800V

KEMA torque, max.: 2Nm

KEMA torque, min.: 1.2Nm

KEMA wire cross-section single core (rigid), min.: 0.2mm²

KEMA wire cross-section single-core (rigid), max.: 16mm²

KEMA wire cross-section stranded, max.: 10mm²

KEMA wire cross-section stranded, min.: 0.2mm²

UL Recognized

UL File Number: E95701

UL Recognized: 1

UL Usegroup B: rated current: 65A

UL Usegroup B: rated voltage: 600V

UL Usegroup C: rated current: 65A

UL Usegroup C: rated voltage: 600V

UL approval: UL 1059

UL factory wiring:

UL field wiring:

UL torque, max.: 17.7Lb In.

UL torque, min.: 10.6Lb In.

UL wire cross-section single-core (rigid) AWG, max.: 6

UL wire cross-section single-core (rigid) AWG, min.: 24

UL wire cross-section stranded AWG, max.: 6

UL wire cross-section stranded AWG, min.: 24

UL wire material: Cu

Environment

Environmental Product Compliance

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2024-06-27

RoHS Conform: Yes

Accessories

Quick marking



PMC SB 7,5/40 WH

9326.7

Markers



PMC SB 7,5/40 So WH

3327.7
